

# T150+

Thermostatic Electric Shower



The Great British Shower Company 



## DESIGN+

### Connectivity

Engineered for automatic compatibility with wired analogue and digital level access waste pumps

### Kit

Contemporary design that can be adapted to individual needs

### Start/Stop

Separate control that allows for the retention of the selected temperature setting

### Installation

Large footprint and removable entry trims for multiple pipe and cable entry

### Thermostatic

Unique Tri-Therm™ thermostatic control to prevent fluctuations in temperature. Complies with BEAB CARE

## SAFETY+

### Controls

Adjustable temperature stop – reduces the risk of accidentally turning the temperature too high

### Communication

Audible feedback for start up and shut down

### Tamper Proof

Control with Safe-Set™, ensure tamper proof, maximum temperature setting whilst allowing full rotation of the temperature dial

### Thermostatic

Constantly regulated temperature gives the user more precise and safe showering – heats water to within  $\pm 1^{\circ}\text{C}$ . Complies with BEAB CARE

## SIMPLICITY+

### Controls

Intuitive low resistance operation

### Installation

Quick and easy to install, taking only 2 minutes to commission

### Kit

Adjustable kit ideal for retrofit projects.

### Communication

Power on illumination

DESIGNED & BUILT IN BRITAIN

NEXT DAY DELIVERY

EASY TO INSTALL

FIT AND FORGET

FULL PARTS & LABOUR GUARANTEED

TRUSTED TRITON SERVICE

INC INCLUSIVE SHOWERING



## Product information

# T150+

## Thermostatic Electric Shower



The Great British Shower Company 

### Shower

Temperature stability	Thermostatic $\pm 1^{\circ}\text{C}$ with Tri-Therm™ (1)
Power ratings	8.5kW & 9.5kW (at 240V)
Finish	White/Chrome
Adjustable max temperature	41°C, 43°C or 47°C with Safe-Set™ (2)
Timed auto shutdown	5, 10, 20 or 30 mins (default 20 mins)
Start/stop type	Electronic soft press button
	Start/stop button & temperature control dial
Audible feedback	Start/stop and timer end confirmation
Visual indicators	Power-on/timer/low flow illumination
Water connection	15mm swivel inlet (up/down)
Terminal block	16mm max cable
Waste pump connection(s)	Analogue & Digital (wired)
Water supply	Mains cold water
Water pressure min	1bar (running at 8 l/min) (3)
Water pressure max	10bar (static)
Removable pipe/cable trims	Top & bottom (15mm pipework & 38mm cable trunking)
Other installation aid(s)	Wall mounting template



### Dura-Flow™ Shower head

Diameter (OD)	110mm
Finish	White
Spray options	5 patterns
Cleaning	Rub clean nozzles & removable spray plate



### Anti-Kink Hose

Length	1.75m
Material	Stainless Steel
Finish	Chrome
Construction	Double interlock



### Product Codes

T150+ 8.5kW Electric Shower	SP1508WP
T150+ 9.5kW Electric Shower	SP1509WP

Contact our specification team

**Call:** 02476 234 776 | **Email:** [specification@tritonshowers.co.uk](mailto:specification@tritonshowers.co.uk) | **Web:** [www.tritonshowers/specifiers](http://www.tritonshowers/specifiers)

(1) Tri-Therm™ constantly regulating flow, blending water and adjusting the power to precisely control the showering temperature.  
 (2) Safe-Set™ tamper proof maximum temperature setting whilst allowing full rotation of the temperature dial.  
 (3) The shower will operate down to 0.5 bar at reduced flow rates.